

CELLULAR RUBBER EPDM

PRODUCT NAME AND CODE

Mikroguma SCP Select [MEP]

TECHNICAL SPECIFICATION

QUALITY	EPDM
SPECIFIC GRAVITY	~ 115 kg/cm ³
COLOUR	czarny
TEMPERATURE	-40°C / +90°C
WATER ABSORPTION	<5%
STRUCTURE	closed cell
OZONE/UV RESISTANCE	good *
RESISTANCE TO THERMAL AGEING	good *
RESISTANT TO OILS AND FUELS	none
RESISTANCE TO ACIDS	medium *

TOLERANCE FOR SPECIFIED VALUES +/- 3% UNLESS OTHERWISE STATED IN THE DATA SHEET

INFORMATION

The information contained in the material data sheet is based on our best knowledge and the results of internal tests. They are indicative and do not constitute a definite guarantee of the properties shown.

The information provided is an indication and cannot be regarded as binding.

We recommend that you carry out verification tests yourself before using the product.

*compared to a general-purpose SBR rubber sheet



BRAND

SCPSELECT

SCP Sp. z o.o.

PRODUCT SPECIFICATION

- Foamed EPDM rubber sheets based on ethylene propylene rubber.
- Products with good resistance to weather, UV and diluted acids.
- Suitable for outdoor and indoor use.
- With improved resistance to thermal ageing.

STORAGE CONDITIONS

- It is recommended to store the product in warehouse conditions at a temperature of +10 to +25°C.
- Avoid direct sunlight and contact with media reacting with the rubber: oils, greases, solvents, fuels, acids, etc.

COMPLIANCE



DISTRIBUTOR

SCP
Rubber Solutions

SCP Ltd | ul. Turystyczna 1, 43-155 Bieruń | www.scp1.pl