

RUBBER FLOORINGS WILLOW (SBR)

PRODUCT NAME AND CODE

WILLOW SCP Select [WML]

TECHNICAL SPECIFICATION

QUALITY	SBR		
THICKNESS	3 mm		
PRODUCT FORM	Roll 1,2 x 10m	Roll 1,4 x 10m	Roll 1,6 x 10m
SPECIFIC GRAVITY	1,5 g/cm ³		
HARDNESS	70 +/-5 Sha		
COLOUR	black		
TEMPERATURE	-20°C / +70°C		
TENSILE STRENGTH	3 MPa		
ELONGATION AT BREAK	150%		
OZONE/UV RESISTANCE	none		
RESISTANCE TO THERMAL AGEING	none		
RESISTANCE TO OILS AND FUELS	none		

TOLERANCE FOR SPECIFIED VALUES +/- 3% UNLESS OTHERWISE STATED IN THE DATA SHEET

INFORMATION

The information contained in the material data sheet is based on our best knowledge and the results of internal tests. They are indicative and do not constitute a definite guarantee of the properties shown.

The information provided is an indication and cannot be regarded as binding.

We recommend that you carry out verification tests yourself before using the product.



BRAND

SCPSELECT

SCP Ltd

PRODUCT SPECIFICATION

- Made from an SBR rubber base. It is a styrene butadiene rubber, usually referred to as general purpose rubber.
- A product with anti-slip, insulating and protective properties.
- Thanks to its flexibility, it adapts well to the ground.
- It has a reflective fabric structure on the underside which increases the effectiveness of the bonding to the substrate when required.
- Each roll is individually wrapped in foil or a bag with a label identifying the product and production batch.
- The product is non-alkaline.

STORAGE CONDITIONS

- It is recommended to store the product in warehouse conditions at a temperature of +10 to +25°C.
- Avoid direct sunlight and contact with media that react with rubber: oils, greases, solvents, fuels, acids, etc.
- It is allowed to store the rolls in layers, but not more than four levels.

COMPLIANCE



DISTRIBUTOR

SCP
Rubber Solutions

SCP Ltd | ul. Turystyczna 1, 43-155 Bieruń | www.scp1.pl

WILLOW (SBR)