

RUBBER SHEETS FOR GENERAL PURPOSES



PRODUCT NAME AND CODE

SBR SCP Select [PSB]

TECHNICAL SPECIFICATION

QUALITY	SBR		
INSERTIONS	without insertions	single cotton	double cotton
SPECIFIC GRAVITY	1,5 g/cm ³		
HARDNESS	70 +/-5 ShA		
COLOUR	black		
TEMPERATURE	-20°C / +70°C		
TENSILE STRENGTH	3,0 MPa		
ELONGATION AT BREAK	150%		
OZONE/UV RESISTANCE	none		
RESISTANCE TO THERMAL AGEING	none		
RESISTANCE TO OILS AND FUELS	none		
RESISTANCE TO ACIDS	none		

INFORMATION

The information contained in the material data sheet is based on our best knowledge and the results of internal tests. They are indicative and do not constitute a definite guarantee of the properties shown.

The information provided is an indication and cannot be regarded as binding.

We recommend that you carry out verification tests yourself before using the product.

BRAND

SCPSELECT

SCP Ltd

PRODUCT SPECIFICATION

- Styrene butadiene rubber referred to as general purpose rubber.
- Products with good abrasion resistance provide an economical alternative to natural rubber.
- The most common type of rubber in many industries.
- Smooth surface on both sides.
- Each plate in the roll is individually wrapped in foil or bag with a label identifying the product and production batch.
- The product is non-alkaline, foil-lined.
- For indoor use in a chemically inert environment.

STORAGE CONDITIONS

- It is recommended to store the product in warehouse conditions at a temperature of +10 to +25°C.
- Avoid direct sunlight and contact with media that react with rubber: oils, greases, solvents, fuels, acids, etc.
- It is allowed to store the rolls in layers, but not more than four levels.

COMPLIANCE



DISTRIBUTOR

SCP
Rubber Solutions

SCP Ltd | ul. Turystyczna 1, 43-155 Bieruń | www.scp1.pl

SBR